

NICMA Anti-Slip Formply

Building Product Information Sheet (BPIS)

Version: 1.0

Issue Date: July 2026

Product Description

NICMA Anti-Slip Formply is a premium film-faced plywood panel manufactured with a durable **textured anti-slip phenolic film surface** designed to provide enhanced grip underfoot. Bonded using a **Weather and Boil Proof (WBP) glue line**, it offers excellent durability, wear resistance, and moisture resistance for demanding commercial, industrial, transport, and construction applications.

The textured surface provides improved slip resistance, while the robust plywood construction delivers strength and durability for applications requiring a hard-wearing, non-slip panel.

Product Range

Thickness (mm) Sheet Size (mm)	
12	2440 x 1220
12	3150 x 1530
18	2440 x 1220
18	3150 x 1530
21	2440 x 1220
21	3150 x 1530

Relevant New Zealand Building Code Clauses

When designed, installed, and maintained in accordance with this document, NICMA Anti-Slip Formply may contribute to compliance with the following New Zealand Building Code clauses:

B2 Durability

NICMA Anti-Slip Formply is manufactured using a **Weather and Boil Proof (WBP) glue line** and a durable phenolic film overlay, providing excellent bond durability and surface performance when installed and maintained appropriately.

F2 Hazardous Building Materials

NICMA Anti-Slip Formply does not contain hazardous materials at levels that would prevent compliance with Clause F2 when used as intended.

Intended Use

NICMA Anti-Slip Formply is intended for non-structural applications including:

- Trailer and truck flooring
 - Loading ramps
 - Industrial walkways
 - Mezzanine flooring
 - Commercial vehicle fit-outs
 - Scaffolding platforms
 - Construction platforms
 - General anti-slip flooring applications
-

Scope of Use

NICMA Anti-Slip Formply may be used where:

- A durable anti-slip plywood panel is required.
 - A WBP bonded plywood panel is specified.
 - The product is installed in accordance with accepted building practices.
 - Appropriate maintenance is carried out for the intended service environment.
-

Limitations on Use

NICMA Anti-Slip Formply:

- Is a non-structural plywood product.

- Must not be used where structural performance is required unless specifically designed and approved.
 - Must not be used as structural bracing, flooring, roofing, diaphragm construction, or other load-bearing applications.
 - Should be suitably protected and maintained where exposed to prolonged weathering or standing water.
 - Must be installed and maintained in accordance with accepted building practices.
-

Design Requirements

The building designer is responsible for ensuring:

- The product is suitable for the intended application.
 - Appropriate fixing methods are specified.
 - Slip resistance requirements are appropriate for the intended use.
 - Moisture exposure and drainage are considered during design.
 - The product is used within its stated limitations.
-

Installation Requirements

- Store sheets flat, dry, and fully supported prior to installation.
 - Install using suitable corrosion-resistant fasteners.
 - Support sheets adequately to suit the intended application.
 - Seal exposed cut edges where required.
 - Follow accepted industry installation practices.
-

Maintenance Requirements

To achieve the expected service life of the product:

- Keep the anti-slip surface clean and free from debris.
- Inspect regularly for wear or damage.
- Repair or replace damaged panels where necessary.
- Ensure drainage is maintained to minimise standing water.

- Inspect exposed edges and reseal if required.

Product Characteristics

Property	Description
Product Type	Film Faced Anti-Slip Plywood
Surface Finish	Textured Phenolic Film
Core Construction	Hardwood
Treatment	Untreated
Bond Type	Weather and Boil Proof (WBP) Glue Line
Edge Profile	Square Edge
Intended Use	Non-Structural Industrial and Commercial Applications

Warning Statement

At the date of publication, NICMA Anti-Slip Formply is not subject to a warning or ban under Section 26 of the Building Act 2004.

Country of Manufacture

China

NICMA Anti-Slip Formply is manufactured by approved overseas manufacturing facilities operating under documented quality control and production procedures.

Importer and Supplier Information

Importer: Nicholls & Maher Ltd

Trading Name: NICMA

Address: 15 Ross Reid Place, East Tamaki, Auckland 2013, New Zealand

Phone: (09) 274 5317

Email: info@nicma.co.nz



Website: www.nicma.co.nz